

Delta 15 Right Angled Stubby WiFi / WLAN Antenna

Key Features

- Compact design: 53.5mm long
- Cable free WiFi antenna solution
- 2.4 to 2.5GHz Operating Frequency
- 2dBi Peak Gain



General Description

The Delta 15 is a direct connect, stubby antenna tuned to 2.4GHz - the WiFi / WLAN / Bluetooth / ZigBee frequencies and is built with a right angled connector.

Despite its small size of 53.5mm in length, it still performs at a high level that most stubby antennas cannot compete with. The Delta 15 offers a small and compact, cable-free antenna solution that is ideal for use with WiFi enabled terminals and modem. Not having to deal with cables makes the job much easier for installers as you simply screw the antenna into the antenna port of your device.

The Delta 15 is commonly used with WiFi, Bluetooth, ZigBee and ISM based applications to help improve the signal strength and better the performance of your short-range terminal. This 2.4GHz antenna can be used with most modern day WiFi modems such as NetGear and TP-link's that operate on the traditional 2.4GHz.

The Delta 15 is supplied, as standard, with a right angle reverse polarity (RP) SMA male connector. This antenna can be built with a connector of your choice for volume requirements.

Please see the Delta 14 for the STRAIGHT connector version of the Delta 15.

Additional Considerations

- Made out of durable TPS for long lasting antenna
- Supplied with a right angled RP SMA connector for direct connection to a device
- Omni directional radiation to ease installation
- RoHS Compliant

Rev 1.1

A member of the Olancha Group Ltd

Siretta Ltd Basingstoke Road Spencers Wood Reading Berkshire RG7 1PW
 sales
 +44(0)118 976 9014

 fax
 +44(0)118 976 9020

 email
 sales@siretta.co.uk

 web
 www.siretta.co.uk




Delta 15 Right Angled Stubby WiFi / WLAN Antenna

Key Specifications - Electrical

| Operating temperature: | -20 to +60°C |
|------------------------|------------------------------|
| Storage temperature: | -30 to +75°C |
| Impedance: | 50 ohm |
| Gain: | 2.0dBi |
| VSWR: | 2.0 max |
| Operating frequencies: | 2400MHz |
| Polarization: | Veritcal |
| Radiation: | Omni |
| Electrical wave: | $\frac{1}{4} \lambda$ dipole |

Key Specifications - Electrical



Key Specifications - Mechanical

| Dimensions: | 53.5mm |
|---------------------|----------------|
| Connector: | SMA RP |
| Mounting method: | Direct connect |

RP SMA Right Angle Plug

